

**Models 4DS, 4MS, 4DSP 600V,
4DSHV 4160v Split & Solid
AC Current Transducers
Custom Sizes Always Available**



4DS & 4MS
Removable
Top Version
and Bus Bar Style Many Sizes
4DS: 2.5, 5.0 * & 10 VDC
4MS: 0-20mA & 4-20mA
Windows from 0.75" to 10"x10"



Tilt Top Split
Current Transducer
Window Openings: 0.5" to 4"
4DS Outputs: 2.5, 5.0 or 10VDC
4MS Outputs: 0-20mA & 4-20mA
0.4", 0.7" 1.25"



Solid Potted
Model 4DSP
Model 4MSP
4DSP Outputs: 2.5, 5.0 * & 10 VDC
4MSP Outputs: 0-20mA & 4-20mA
Accuracy: +/- 1% Standard
Call for higher accuracies
8 foot standard red and black



Model 4DSHV
Model 4MSHV
SPLIT 4160 Volt Medium Voltage
Window sizes 2"x2" to 10"x10"
Accuracy +/- 1% at full scale
Input ranges 100A to 4000A
20KV leads 8 feet long standard
Internally encapsulated/potted



1545 Commercial St NE, Salem, OR 97301
1-503-370-7377 sales@sentrancorp.com